

Specifications:

- Pump up to 1/2 Gallon Per Minute and as low as 40mL per minute*
- Suction lift up to 26 feet
- Comes complete with pump head
- AC adapter for 120 volts. For international use, The Alexis has the ability to operate on 220 volts direct with correct mini-transformer (Item # CONVERT 220V/110V) **Please Note: The International Voltage Converter is sold separately upon request**
- Product Dimensions: Width 18" x Depth 8 1/2" x Height 13 1/2"
- Weight of Product: 37 Pounds
- Please Note: Use Masterflex (MF) or other quality silicone tubing comparable to:
 - MF# LS 15: 3/16" ID X 3/8" OD
 - MF# LS 24: 1/4" ID X 7/16" OD
 - [MF# LS 36: 3/8" ID X 5/8" OD](#)

***The Alexis AC to DC inverter is compatible with 220 volts with the purchase of a 220 volt to 120 volt AC step down transformer. You can purchase this step-down transformer in your country.**

Masterflex Easyload™ 2 pump head is a registered trademark of Thermo Fisher Scientific

* Test conducted with 3 feet of size 36 Masterflex™ tubing

What is included:

- 12 Volt Alexis® Peristaltic Pump V3.0 (Item# ALXPERRI-20000)
- VMAX 3.3 Amp Charger For Alexis Pump (Item# PERRY-37200)
- 12 Volt DC to 120/220 Volt AC Power Inverter (Item# PERRY-37300)
- Cigarette Style Female Plug with Battery Clamps (Item# PERRY-34050)