

**PROACTIVE ENVIRONMENTAL PRODUCTS®**  
**Stainless Steel Mega-Monsoon® XL**  
 (Lifts 170 Feet / 52 Meters DTW)



**REQUIRES:**



Low Flow with Power Booster  
3 LCD XL Controller

The Stainless Steel Mega-Monsoon® XL pump is capable of pumping up to 170 feet from ground level (DTW)\* by simply connecting the Stainless Steel Mega-Monsoon® XL to the [Low Flow with Power Booster 3 XL "LCD" Controller](#), then to a 12 volt deep cycle battery, energizing the pump. Sound Simple? We think so. Its reliable design is perfect for continuous purging of groundwater wells. Proactive's Stainless Steel Pumps are patented for their unique design. Simple to use and extremely powerful!

**So why choose the Stainless Steel Mega-Monsoon® XL?**

- The Stainless Steel Mega-Monsoon® XL can operate under harsh conditions with higher turbidity.
- The Stainless Steel Mega-Monsoon® XL has been installed in thousands of remediation sites using pump and treat systems.
- The Stainless Steel Mega-Monsoon® XL can also be used with solar panels for long term groundwater remediation.
- Simple to use! Runs off a deep cycle 12 volt battery.
- Lifts up to 170 feet deep from ground level to water level!
- Reliable design is suitable for continuous purging of groundwater wells.
- Low Flow Sample as low as 10 mL/s per minute, from any depth, when using the [Low Flow with Power Booster 3 XL "LCD" Controller](#) and [SS Non-Return Check Valve](#) (Sold Separately).
- Lift liquid from 350+ feet in 2" and larger diameter wells when using the Proactive Environmental Products® [Stainless Steel Drop Tube and Weight Combo](#)
- Easy to read LCD display conveniently placed on top of the Low Flow with Power Booster 3 XL "LCD" Controller makes adjusting and reading the discharge rate a breeze!
- Computer engineered bottom debris filter screen allows operation under harsh conditions with higher turbidity.
- Long lasting, high performance pump motor module lasts over 400 hours under normal working conditions.
- Simple to clean and decontaminate!

The Stainless Steel Mega-Monsoon® XL is only 1.82" OD and constructed of three high polished stainless steel parts:

1. The replaceable motor module
2. The motor module 3 Pin Bayonette Connector
3. The outside Stainless Steel Housing and Stainless Steel Bottom Inlet Filter Screen

The main wear out parts consisting of the motor and seal all have been incorporated in a single replaceable motor module. Should the existing replaceable motor module fail in the field, a new replaceable motor module can quickly be installed within 30 seconds by a simple quarter turn twist! Once installed, your pump is essentially new and will have a life span identical to a new pump.

\* Depth to water

### Specifications:

WATT CONSUMPTION (MAX):	585 WATTS (MAX)
DC VOLT RECOMMENDATION:	12-15 DC (direct current) At Source
AMP CONSUMPTION (MAX):	39 AMPS
MEASUREMENTS:	LENGTH 7.5" / DIAMETER: 1.82"
CONSTRUCTED:	HIGH POLISH STAINLESS STEEL
REQUIRED TUBING:	3/8" ID POLY TUBING, TEFLON WIRE OPTIONAL
SUPPLIED WITH:	180 FEET OF HEAVY DUTY 10 GAUGE PVC WIRE NEATLY ROLLED UP ON A TUBULAR METAL REEL WITH PUMP HOLDER, 2 MOTOR MODULES, DISPOSABLE LOW FLOW CONTROL VALVE, AND WRENCH

### What is included in the box:

- Stainless Steel Mega-Monsoon® XL Pump (Item# PS-10420)
- SS Mega-Monsoon XL Replaceable Motor Module (Item# PA-14070)
- Low Flow Control Valve (Item# PA-14080)
- Wrench (Item# PA-16089)

<b>Pumping Depth in Feet DTW (Depth To Water)</b>	<b>Gallons Per Minute At 12.5 Volts At The Source</b>
---	---

10	3.25
20	3.00
40	3.00
50	2.75
70	2.50
80	2.25
90	2.25
100	2.00
120	1.75
140	1.25
150	1.00
170	0.25

Test was conducted with a Power Supply at 13.8 volts.

Running your vehicle while using this pump  
will dramatically increase purge volume